


SX08FRO230-01

NWAV™ X-Pol Antenna

8-port 2 ft 30° panel antenna 617-960, 1695-2700, 3400-4200, 5150-5925 MHz:

2 ports 617-2700 MHz, 4 ports 3400-4200 MHz, and 2 ports 5150-5925 MHz

- X-Pol, DAS, and Small Cell multi-port antenna
- Suitable for pole or building mount
- 4x4 MIMO for 3400-4200 MHz
- 2x2 MIMO for 617-2700 and 5150-5925 MHz
- Fast Roll Off pattern performance
- Cost-effective solution for neutral host locations



Electrical specification (min/max)	Ports 1, 2							
Frequency bands, MHz	617-798	824-894	897-960	1695-1880	1850-1990	1920-2180	2300-2400	2496-2690
Polarization	± 45°			± 45°				
Average gain, dBi	12.7	13.0	13.2	13.5	14.2	15.1	15.4	14.8
Horizontal beamwidth (HBW), degrees ¹	39.8°	33.7°	33.1°	35.2°	28.7°	25.2°	24.2°	23.6°
Vertical beamwidth (VBW), degrees ¹	39.1°	33.5°	33.5°	36.5°	29.6°	24.2°	23.4°	23.8°
Fixed electrical downtilt (EDT), degrees	0°							
Cross-polar isolation, port-to-port, dB ¹	25			25				
Max VSWR / return loss, dB	1.5:1 / -14.0			1.5:1 / -14.0				
Max PIM (3rd order, 2x20W) dBc	-153			-153				
Maximum input power port, watts	250			125				

Electrical specification (min/max)	Ports 3, 4, 5, 6	Ports 7, 8
Frequency bands, MHz	3400-4200	5150-5925
Polarization	± 45°	± 45°
Average gain, dBi	14.1	5.5
Horizontal beamwidth (HBW), degrees ¹	29.1°	46.0°
Vertical beamwidth (VBW), degrees ¹	37.0°	33.5°
Fixed electrical downtilt (EDT), degrees	0°	
Cross-polar isolation, port-to-port, dB ¹	25	25
Max VSWR / return loss, dB	1.5:1 / -14.0	1.5:1 / -14.0
Max PIM (3rd order, 2x20W) dBc	N/A	
Maximum input power, watts	50	10

¹ Typical value over frequency.

Note: Vertical beam upper side lobe at 5150-5250 MHz < -12 dB at > 30° above horizon

Mechanical specifications

Dimensions height/width/depth, inches (mm)	24.0/ 24.0/ 8.5 (610/ 610/ 216)
No. of RF input ports, connector type, and location	8 x 4.3-10 female, back
RF connector torque	96 lbf-in (10.85 N·m or 8 lbf-ft)
Net antenna weight, lb (kg)	22.0 (9.9)
Weight with supplied bracket, lb (kg)	27.2 (12.3)
Shipping weight, lbs. (kg)	29.5 (13.4)
Supplied bracket kit	91900324 (included)
Mechanical down-tilt range	+/- 25° lateral (azimuth adjustment) and +/- 25° vertical (up/down tilt)
Rated wind survival speed, mph (km/h)	120 (193) with 91900324 bracket kit and 150 (241.4) with 919017 bracket
Frontal wind loading @ 150 km/h, lbf (N)	26.6 (118.4)
Equivalent flat plate @ 100 mph and Cd=2, sq ft	0.54

Front view	Back view	Side view
	<p>Refer to JMA weep hole modification guide at jmwireless.com for mandatory drilling instructions.</p> <p>The SX antennas can be painted in accordance with the JMA painting guidelines at jmwireless.com</p>	

Array topology	Connector View																				
<table border="1"> <thead> <tr> <th>Array ID</th> <th>Band</th> <th colspan="2">RF port</th> </tr> </thead> <tbody> <tr> <td>R1/Y1</td> <td>617-960/1695-2700</td> <td style="background-color: red;">1-2</td> <td style="background-color: yellow;">1-2</td> </tr> <tr> <td>P1</td> <td>3400-4200</td> <td colspan="2" style="background-color: purple;">3-4</td> </tr> <tr> <td>P2</td> <td>3400-4200</td> <td colspan="2" style="background-color: purple;">5-6</td> </tr> <tr> <td>O1</td> <td>5150-5925</td> <td colspan="2" style="background-color: orange;">7-8</td> </tr> </tbody> </table>	Array ID	Band	RF port		R1/Y1	617-960/1695-2700	1-2	1-2	P1	3400-4200	3-4		P2	3400-4200	5-6		O1	5150-5925	7-8		
Array ID	Band	RF port																			
R1/Y1	617-960/1695-2700	1-2	1-2																		
P1	3400-4200	3-4																			
P2	3400-4200	5-6																			
O1	5150-5925	7-8																			

Ordering information

Antenna model	Description
SX08FRO230-01	2F X-Pol 8-port panel 30°, 4.3-10
919055	Optional inverted mounting kit for 4.0-10.0 in. OD pole
91900313	Optional bracket kit for extended horizontal and vertical tilt ranges