



WPS-2RT-14S

Weather Protection System: 2.2-5 & NEX10 Right Angle 1/4" Superflex Connections



[Installation instructions](#)



[WPS cross-reference chart](#)



Contact technical support:
1-888-201-6073
techsupport@jmawireless.com

General	Specification			
Cables supported	Andrew	FSJ1-50A	RFS	SCF14-50J
		FSJ1RK-50B		SCF14-50JFN
		PTS1-50-P	Eupen	EC1-50-HF
	Hansen	RF5014S	Times	SPP-250-LLPL
		RF5014SZ		SPO-250
	HUBER+SUHNER	SUCOFEEED 1/4 HFFR		
SUCOFEEED 1/4 HF				
Dimensions in. (mm)	3.14 x 1.55 (76.2 x 39.4)			
Weight	0.77 lb 21.8 g			
Material	Silicone rubber			
Lubricant	Dow Corning Molykote® III			
Reusability	Unlimited			

Environmental	Specification	Comment
Installation temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Operating temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Storage temperature	-55 °C to +85 °C (-67 °F to 185 °F)	
Moisture resistance	No leakage	ANSI/SCTE 60 2004, IP-67, IP-68
Corrosion resistance	1000 hours	ASTM B117
U.V. resistance	Exposure to UV light for 1000 hours per ASTM G 53 using UVB-313 type lamps	
H.A.L.T.	40 hours	
Fire rating	UL94 HB	

01/12/24