



WPS-4MT-14S

Weather Protection System: Type N, 4.1-9.5 DIN, & 4.3-10 1/4"
Superflex Connections



[Installation instructions](#)



[WPS cross-reference chart](#)



Contact technical support:
1-888-201-6073
techsupport@jmawireless.com

General	Specification	Comment
Cables supported	Andrew FSJ1-50A, FSJ1RK-50B, PTS1-50-P RFS SCF14-50J, SCF14-50JFN Hansen RF5014S, RF5014SZ Eupen EC1-50-HF Times SPP-250-LLPL, SPO-250 HUBER+SUHNER SUCOFEED 1/4 HFFR, 1/4 HF	
Dimensions in. (mm)	3.450 x 1.400 (87.63 x 35.56)	
Weight	0.053 lb 24.0 g	
Material	Silicone rubber	
Lubricant	Dow Corning Molykote® III	
Reusability	Unlimited	

Environmental	Specification	Comment
Installation temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Operating temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Storage temperature	-55 °C to +85 °C (-67 °F to 185 °F)	
Moisture resistance	No leakage	ANSI/SCTE 60 2004, IP-67, IP-68
Corrosion resistance	1000 hours	ASTM B117
U.V. resistance	Exposure to UV light for 1000 hours per ASTM G 53 using UVB-313 type lamps	
H.A.L.T.	40 hours	
Fire rating	UL94 HB	

02/26/24