



# WPS-4RT-14S

Weather Protection System: Type N, 4.1-9.5, & 4.3-10 Right Angle 1/4" Superflex Connections



[Installation instructions](#)



[WPS cross-reference chart](#)



Contact technical support:  
1-888-201-6073  
[techsupport@jmawireless.com](mailto:techsupport@jmawireless.com)

General	Specification			
<b>Cables supported</b>	JMA Wireless	JMA14S-50	RFS	SCF14-50J
		JMA14SP-50		SCF14-50JFN
	Andrew	FSJ1-50A	Eupen	EC1-50-HF
		FSJ1RK-50B	Times	SPP-250-LLPL
		PTS1-50-P		SPO-250
	HUBER+SUHNER	SUCOFEEED 1/4 HFFR	Hansen	RF5014S
SUCOFEEED 1/4 HF		RF5014SZ		
<b>Dimensions in. (mm)</b>	3.33 x 1.52 (84.6 x 38.6)			
<b>Weight</b>	0.064 lb   29.0 g			
<b>Material</b>	Silicone rubber			
<b>Lubricant</b>	Dow Corning Molykote® III			
<b>Reusability</b>	Unlimited			

Environmental	Specification	Comment
<b>Installation temperature</b>	-40 °C to +65 °C (-40 °F to 149 °F)	
<b>Operating temperature</b>	-40 °C to +65 °C (-40 °F to 149 °F)	
<b>Storage temperature</b>	-55 °C to +85 °C (-67 °F to 185 °F)	
<b>Moisture resistance</b>	No leakage	ANSI/SCTE 60 2004, IP-67, IP-68
<b>Corrosion resistance</b>	1000 hours	ASTM B117
<b>U.V. resistance</b>	Exposure to UV light for 1000 hours per ASTM G 53 using UVB-313 type lamps	
<b>H.A.L.T.</b>	40 hours	
<b>Fire rating</b>	UL94 HB	

03/05/25